



K-G60

Remote Control Gas Detector



Remote operation



Full software calibration function



Multi-signal output



Chinese-English switching



K-G60 Remote Control Fixed Gas Detector

This intelligent gas detector is a fixed type of instrument that continuously monitors the concentration of flammable gas, oxygen concentration or toxic and harmful gas in the working environment.

The detector detects the gas concentration by natural diffusion method, and adopts imported electrochemical sensor, catalytic combustion sensor, infrared sensor or PID sensor, which has excellent sensitivity and excellent repeatability; LCD liquid crystal suitable for factory application displays the concentration value of leaked gas in real time. , immediately start the sound and light alarm signal or drive the exhaust system beyond the preset alarm point.

The international standard 4-20mA signal can be directly connected to the factory DCS system and PLC, and the RS485 digital signal is connected with the factory host computer; the instrument adopts embedded micro-control technology, which is easy to operate and complete in function.



Technical Parameters

| | | | |
|-------------------------|--|-------------------------|--------------------------------|
| Sensor: | Electrochemical, catalytic combustion, semiconductor, PID, infrared gas sensor | | |
| Transfer Method: | Standard 4-20mA signal; Standard RS485 signal; Standard MODBUS RTU protocol; Optional 433 MHz wireless transmission function | | |
| Sampling: | Diffusion/pump-in/Online Monitoring | Explosion-proof: | Exib IIC T6 Gb |
| Volts: | DC24V ± 15% | Response Time: | ≤ 30S |
| Linear error: | ≤ ± 1%F.S | Connect Method: | M20 × 1.5、G1/2 |
| Accuracy: | ≤ ± 3%F.S | Dimension: | 200(L)*181(W)*90(H)mm 1.6kg |

Distributor :