

Portable Dehumidifier

DJ-901T / DJ-1301T / DJ-1501T



- Ambient humidity LCD display timely
- Humidity control set freely, accuracy to ±3%
- Continuously drainage by external soft tube
- Timed shut down setting
- Humidity sensor malfunction alert
- High efficiency, energy saving
- Large rear wheels to adapt to various road conditions.
- Stainless steel handle, portable push-pull
- Automatic defrosting when the ambient temperature is below 18 °C
- World famous brand compressor, 3 minutes delay protection

Model number	DJ-901T	DJ-1301T	DJ-1501T
Dehumidify capacity(30 °C 80%RH)	90L/D	130L/D	150L/D
Power supply	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Rated input power	1.25kW	1.35kW	1.8kW
Rated input current	5.8A	6.2A	8.5A
Circulating air flow	800m³/h	950m³/h	1200m³/h
Applying area	90-120m²	100-130m²	130-150m²
Humidity control range	40%-95%	40%-95%	40%-95%
Drainage way	Hose connection	Hose connection	Hose connection
Working temperature range	5~38°C	5~38°C	5~38°C
Refrigerant	R407c/R410a	R407c/R410a	R407c/R410a
Noise	≤60dB	≤60dB	≤60dB
Compressor type	Rotary	Rotary	Rotary
Warranty	1 Year	1 Year	1 Year
Standard packaging	Wooden Case	Wooden Case	Wooden Case
Certification	CE	CE	CE
Net weight/Gross weight	62kg/80kg	64kg/82kg	65kg/83kg
Machine size	620*560*940mm	620*560*940mm	620*560*940mm
Package size	645*665*1115mm	645*665*1115mm	645*665*1115mm